
ZENEN
ELECTRIC POWER

COPPER CABLE LUG

www.czenen.cn

Application: Used for connection of copper cable with copper end of electrical equipment in low voltage. From 6 to 800 mm²,
Material: Cu ≥ 99.9%;Surface: tin plated





Standard: DIN 46235

Type	Conductor Size (mm^2)	Dimensions				Stud Size
		L(mm)	d(mm)	D(mm)	B(mm)	
AUS6-5	6	24	3.8	5.5	8.5	M5
AUS6-6		24	3.8	5.5	9	M6
AUS6-8		24	3.8	5.5	13	M8
AUS10-5	10	27	4.5	6	9	M5
AUS10-6		27	4.5	6	9	M6
AUS10-8		27	4.5	6	13	M8
AUS16-6	16	36	5.5	8.5	13	M6
AUS16-8		36	5.5	8.5	13	M8
AUS16-10		36	5.5	8.5	17	M10
AUS16-12		36	5.5	8.5	18	M12
AUS25-6	25	38	7	10	14	M6
AUS25-8		38	7	10	16	M8
AUS25-10		38	7	10	17	M10
AUS25-12		38	7	10	19	M12
AUS35-6	35	42	8.2	12.5	17	M6
AUS35-8		42	8.2	12.5	17	M8
AUS35-10		42	8.2	12.5	19	M10
AUS35-12		42	8.2	12.5	21	M12
AUS50-8	50	52	10	14.5	20	M8
AUS50-10		52	10	14.5	22	M10
AUS50-12		52	10	14.5	24	M12
AUS50-14		52	10	14.5	24	M14
AUS50-16		52	10	14.5	28	M16
AUS70-8	70	55	11.5	16.5	24	M8
AUS70-10		55	11.5	16.5	24	M10
AUS70-12		55	11.5	16.5	24	M12
AUS70-14		55	11.5	16.5	24	M14
AUS70-16		55	11.5	16.5	30	M16
AUS90-8	95	65	13.5	19	28	M8
AUS90-10		65	13.5	19	28	M10
AUS90-12		65	13.5	19	28	M12
AUS90-14		65	13.5	19	28	M14
AUS90-16		65	13.5	19	32	M16
AUS120-8	120	70	15.5	21	31	M8
AUS120-10		70	15.5	21	32	M10
AUS120-12		70	15.5	21	32	M12


ZENEN
ELECTRIC POWER

COPPER CABLE LUG

www.czenen.cn

Application: Used for connection of copper cable with copper end of electrical equipment in low voltage. From 6 to 800 mm², Material: Cu ≥ 99.9%;Surface: tin plated





Standard: DIN 46235

Type	Conductor Size (mm^2)	Dimensions				Stud Size
		L(mm)	d(mm)	D(mm)	B(mm)	
AUS120-14		70	15.5	21	32	M14
AUS120-16		70	15.5	21	32	M16
AUS150-10	150	78	17	23.5	34	M10
AUS150-12		78	17	23.5	34	M12
AUS150-14		78	17	23.5	34	M14
AUS150-16		78	17	23.5	34	M16
AUS185-10	185	82	19	25.5	37	M10
AUS185-12		82	19	25.5	37	M12
AUS185-14		82	19	25.5	37	M14
AUS185-16		82	19	25.5	37	M16
AUS185-20		82	19	25.5	40	M20
AUS240-12	240	92	21.5	29	42	M12
AUS240-14		92	21.5	29	42	M14
AUS240-16		92	21.5	29	42	M16
AUS240-20		92	21.5	29	45	M20
AUS300-12	300	100	24.5	32	48	M12
AUS300-14		100	24.5	32	48	M14
AUS300-16		100	24.5	32	48	M16
AUS400-16	400	115	27.5	38.5	55	M16
AUS400-20		115	27.5	38.5	55	M20
AUS500-14	500	125	31	42	60	M14
AUS500-16		125	31	42	60	M16
AUS630-16	630	135	34.5	44	64	M16
AUS630-20		135	34.5	44	64	M20
AUS800-20	800	165	40	52	75	M20

+86-137-3808-0812
overseas@czenen.cn
+ 86 (577) 6161 8066
No. 332 Transportation West Road, Yueqing, Wenzhou City, China
www.czenen.cn